



Product Data Sheet

CALCINED KAOLIN DG80

Product Description:

DG80 calcined kaolin is a popular type grade with high brightness, reasonable particle distribution and medium oil absorption. It is providing good opacity and tinting ability in coating formulation performing as extender of titanium dioxide. It is also a high cost effective functional filler for paper, plastic, rubber, electrical wire etc.

Chemical Name: Anhydrous aluminium silicate

Main Application: Coating, paper, plastic, rubber, electrical wire.

Typical Properties:

Properties	Standard
Brightness (TAPPI, %)	≥95
Brightness (ISO R457, %)	≥93
Particle size (-2µm, %)	80±2
Average particle size (D50,µm)	0.9±0.1
Screen residue (325 mesh, %)	≤0.005
Oil absorption (g/100g)	60±5
Moisture (%)	≤0.5
pH	6.0-8.0

Chemical Composition:

SiO ₂ (%)	Al ₂ O ₃ (%)	Fe ₂ O ₃ (%)	TiO ₂ (%)	CaO (%)	Na ₂ O (%)	K ₂ O (%)	MgO (%)
52±2	45±2	≤0.8	≤1.3	≤0.5	≤0.2	≤0.1	≤0.2

This average technical information is the result of extensive research and testing by the producers and others and is given in good faith and in the belief that it is accurate. However no guarantee of accuracy is made nor can we anticipate every possible application or variation in manufacturing technology or usage. Therefore the product is sold without warranty, express or implied and on the condition that purchasers determine the suitability of the product for their particular purpose by conducting their own tests. No liability can be accepted for the infringement of any patents.